



Original Research Paper

ECOBIN: A SOPHISTICATED APPROACH TO WASTE MANAGEMENT

B. Ravi Chandra¹, V. Venkatesh², B. Anil Kumar³, P. Sai Ram⁴, Dr. I Sharath Chandra⁵ and Ajay Roy⁶

^{1, 2, 3, 4} G.Pullaiah College of Engineering and Technology, Kurnool, India

⁵Matrusri Engineering College, Hyderabad, India

⁶College of Engineering, University of Bisha, Saudi Arabia

¹chandrabc11@gmail.com, ²Venkatvenky7075@gmail.com, ³anilkumarbelagala@gmail.com, ⁴rsai9935@gmail.com,

⁵Sharath.inguva@gmail.com and ⁶aroy@ub.edu.sa

ABSTRACT

In this study, we present a waste management system that uses GPS and GSM wireless technology to separate trash and keep tabs on it. In order to keep the environment clean, intelligent waste management is crucial. Reason being, modern society's biggest problem is disorganized and non-systematic garbage collection. Consequently, we must find a way to gather trash efficiently. We have provided an integrated platform for trash segregation and monitoring as a solution to this challenge. An embedded system will monitor the quantity of garbage placed. The trash is first classified into dry, metal, and wet categories during segregation. Then, during monitoring, sensors are inserted in the bins containing dry and wet waste, and the level of each bin is relayed via GSM with GPS locations. In addition to offering a cost-effective option for collecting vast amounts of data, The Internet of Things, or IoT, is a network of linked computers that can send data without requiring human intervention.

Keywords: *Smart waste management, GPS and GSM technology, Smart cities, Sensor-enabled bins, Waste segregation, Environmental sustainability, Automated waste management system.*

1. INTRODUCTION

There has been a steady increase in the Population rate. Lots of issues arise as a result of this. Rising garbage production is a big issue; at present, India generates 42.0 million tons of garbage annually, and its collection efficiency is low. Pollution, ecological disruption, unpleasant odors, and improper trash collection all contribute to a more unsanitary environment, which in turn may increase the prevalence of illnesses. The main problem with poor collection is that trash cans in public spaces are often overflowing [1]. According to a recent report, the Central Pollution Control Board (CPCB) estimates that India produces over 26,000 tons of plastic every day, with little more than 10,000 tons of rubbish going uncollected. The Energy Resources Institute (TERI) conducted another poll in which over 90% of respondents said that there were moderate to severe health concerns associated with inappropriate waste management in India. Eight cities were surveyed in this study: Coimbatore, Delhi, Guwahati, Indore, Jamshedpur, Kanpur, Mumbai, and Pune. All things pertaining to garbage were included in the study. Nearly half of the population experienced improper garbage collection due to these concerns. Appropriate measures

must be implemented to resolve these issues. The solution to the problem of data gathering is presented in this study as an embedded IoT system. The term "embedded" refers to a type of hardware that is self-contained and does not require an operating system. Instead, it employs a microcontroller or microprocessor, which are programmable devices that carry out specific functions as specified by the user. The Internet of Things (IoT) is applicable in all fields since it facilitates the creation of efficient techniques and systems that improve people's lives and present new, promising, and cost-effective solutions. One solution to the problem of garbage collecting is an embedded IoT system. As shown before, it is composed of two sections: the isolation section and the monitoring section. Segregation is all about collecting garbage and then sorting it into dry and moist categories. The mechanical portion of the separation comprises a conveyor belt that sorts garbage. If the waste is wet, a moisture sensor detects it and puts it in the damp bin; otherwise, it goes to the dry bin. A cloud server is a strong physical or virtual infrastructure that handles data processing and storage for applications. When the level of these wastes reaches a certain threshold, an ultrasonic sensor will send the data to a

*Corresponding Author:

Received: 25th Feb, 2026; Revised: 6th June, 2026; Accepted: 8th July, 2026; Available Online: 14th Sep, 2026

(DOI): 10.70102/AEJ.2026.18.6s.22

cloud server through MQTT. This data can then be retrieved from any location at any time. Messaging Quick Transactions (MQTT) is a lightweight network protocol that allows devices to exchange messages using a publish-subscribe mechanism. For data transport, this protocol uses TCP/IP. It comes with solid assurances of delivery. Smart waste management solutions—like those covered in [20]—can help lower operational costs and environmental risks by greatly increasing commercial garbage collecting efficiency. Furthermore, including blockchain technology—as discussed in [21]—can improve waste disposal record security and openness. Recent work also emphasizes that improved collection, recycling infrastructure, and circular-economy resource management are important for reducing the environmental burden of waste streams [14].

2. LITERATURE SURVEY

Ineffective waste management techniques, a lack of systematic trash collection and management plans, and improper garbage discharge have all contributed to significant environmental problems and costly disposal costs. Several researches on trash management have focused on GPS and GSM technology to address the aforementioned challenges in solid waste management, thanks to the favorable effects of wireless services. Effective waste management procedures and sustainability concepts are critical in the construction, food processing, and related industries because of the continually high residue content in their trash. Waste management technology has been the subject of several publications. To save energy and extend the life of garbage cans, Poddar et al. [1] suggested a system that monitors when cans are full and sends the information over a wireless mesh network. Recent studies further demonstrate that sustainable waste management can combine physicochemical treatment and biological valorization approaches, including portable wastewater treatment and microbial conversion of organic waste [23,24].

Furthermore, smart bins that minimize power consumption and increase operational lifetime through a duty cycle approach were tested in outdoor settings. The results showed that the technique is feasible, but there are still some unsolved implementation issues. In order to facilitate effective decision-making and real-time monitoring, Aazam and Mohammad [2] presented an innovative waste management system that is cloud-based and makes use of GPS and GSM. Similarly, the "Smartbin" system was created by Folianto et al. [3] to optimize trash management procedures through the use of intelligent sensor networks. To significantly enhance energy optimization in smart city monitoring wireless sensor networks, Sundhari and Jaikumar [4] introduced an Internet of Things (IoT)-assisted architecture that uses Hierarchical Computation Strategic Making (HCSM) and Dynamic Stochastic Optimization Techniques (DSOT). In addition, Chaudhari and Patil detailed a system for

managing garbage collection in cities that rely on the Internet of Things [5]. Vasconcelos Sobra and Oliveira [7] assessed the functionality of MQTT brokers in Internet of Things (IoT) applications, with a focus on how well they transmit data for smart cities, while Al-Masri et al. [6] presented "Recycle.io," an Internet of Things (IoT)-enabled framework that simplifies garbage sorting and collection. Simultaneously, Swamy et al. [8] examined the time-differenced double difference technique for NavIC receiver differential phase bias measurements, which offer vital information for improving satellite navigation systems. Moreover, utilizing a double-difference approach with zero and short base length carrier phase measurements, Swamy et al. [9] examined the quality of L5 signals from Indian Constellation satellites. Further evidence of these navigational gains, especially during geomagnetic storms and solar flares, is shown in Swamy et al. [10], who establish a link between the rate of TEC index and location inaccuracy. Research like this shows how smart cities may use accurate navigation data to monitor and improve their garbage management in real time. Future data analysis, according to Muthuraman et al. [12], will be conducted as a web application using statistics gathered by sensor technologies. Using sensors built in garbage cans to track fill levels, this system links with route optimization software. It also usually features a simple smartphone app for locals to improve access. Priyadharshini et al. [13] investigate the spread of IoT across several sectors, therefore addressing essential issues, including risk considerations, security concerns, and implementation hurdles. This sophisticated technology not only helps waste management companies but also improves citizens' quality of life and supports environmental sustainability by offering timely information and services linked with waste disposal and recycling. Moreover, blockchain-based IoT solutions like those in [21] can improve security in waste monitoring systems for smart cities, guaranteeing unchangeable documentation of garbage disposal operations. As illustrated in [20], future advancements in innovative waste management systems could use IoT solutions supported by blockchain technologies to improve commercial garbage collection methods through automated data tracking. More broadly, recent smart-system research shows that IoT-enabled sensing, data analytics, and automated decision support can improve resource monitoring and operational efficiency, providing a useful methodological direction for intelligent waste systems [17]. Recent treatment-oriented research also shows that portable electrocoagulation can support decentralized wastewater management by reducing contaminant loads at the point of generation [15]. Biological studies on waste-derived microorganisms further demonstrate the potential for recovering useful microbial functions from organic waste streams [16].

3. EXISTING SYSTEM

The literature contains a broad spectrum of waste management-oriented research projects. The authors of [14] present an intelligent disposal system fitted with sensors to monitor garbage accumulation inside the enclosure and driven by solar energy. Should necessary, the container can compress the trash, lowering its volume by up to 10 times before collection. The SENSONEO waste monitoring system [15] combines a citizen app, a sophisticated waste management system, and smart sensors. These intelligent sensors provide the data to the waste management system after measuring filling levels in several containers many times daily using ultrasonic technology. The container is split up into several pieces for easy monitoring. The authors in [16] suggest a novel method of solid waste management using an integrated sensing system. This system automates garbage management using mobile app-based monitoring and cloud computing. The proposed brilliant garbage container improves efficiency by using ultrasonic sensors and many gas sensors. Authors in [17] assess trash bin contents and send the data to a central server over the Internet using an IoT-based innovative waste management system. In [18], a novel technique presents an intelligent container meant to stop waste from dumping outside the bin. This approach uses infrared sensors to track both the inside and outside of the chamber. Moreover, the system detailed in [19] offers a way to avoid constant monitoring around the clock. It uses ultrasonic sensors to quickly ascertain the waste levels in dumpsters and a well-organized, automated method for selective waste clearance. Modern waste management systems can automate tracking, guarantee

transparency, and improve waste disposal efficiency by including IoT, cloud storage, and blockchain technologies—as emphasized in [20] and [21]. Biological treatment studies also show that targeted microbial cultures can reduce pollutant loads in domestic wastewater, complementing sensor-based monitoring with sustainable treatment strategies [18].

4. PROPOSED SYSTEM

Under the current method, the firm collects garbage either once every week or every two days. Despite the fact that trash stinks, it overflows the trash can and then spreads across the roadways, polluting the environment. The pungent odor contributes to air pollution and the transmission of illness. The new garbage collection system, based on the IEEE 802.11 standard, has problems with accurate updates and timely pickup of rubbish, and the fact that street dogs and other animals devour the waste food spreads filth all over the place. Systems for the management of waste have been around for quite some time. Current Waste Management methods are highly dependent on human involvement. There are local bins strategically located all across the city. Manual laborers visit each bin at predetermined intervals to check its capacity, fill it up if necessary, and then empty it before moving on to the next bin. The manual laborers must examine the bins' state on a regular basis. It takes a lot of time and energy to do this. Moreover, organizations or governments incur material and financial losses due to the dumping of all wastes into the same treatment process, which is caused by the absence of organized waste clearing and the informal separation of material wastes into organic and inorganic, wet and dry waste.

Block diagram




Fig 1. Proposed Circuit Diagram for Automatic Waste Management

5. WORKING MODEL

This block diagram is the prototype for our project, Automated Garbage Sorting Bin Waste Segregation

System. This block schematic is the prototype for our Automated Waste Segregation Bin Garbage Sorting System. The garbage segregator is made to make it easier

to throw away garbage. Wet trash, metal trash, and dry trash are the three categories that make up the system. Various sensors, such as a moisture sensor and a metal sensor, are integrated into the conveyor belt system, which sorts the incoming garbage according to its moisture content and then directs it to the appropriate bin. The servo motors are configured to deflect in accordance with the working. This makes it easier to treat various types of garbage according to what is needed. The entire arrangement automates the process, which means less human interaction is required for waste segregation, and the bins are successfully collected. Consequently, modern waste management is a significant concern. There is a lot of room for improvement and prevention if garbage is managed correctly from the source. Proper trash disposal and the implementation of the R.I.R.E. principle can be facilitated by sorting trash into wet, metal, and dry categories. Decomposition of the damp waste results in plant manure, whereas recycling is an option for dry waste. Therefore, the Automatic trash Segregator is quite helpful for trash management. The monitoring component involves calculating the distance between the trash can and an ultrasonic sensor, which then determines the amount of trash within. The authorized individual receives updates on the position of these bins using GPS and GSM. They include dust, metal, and moist waste.

5.1 Hardware Requirements:

Any operating system or software program's most typical set of needs is for the hardware or actual computer resources. A list of hardware compatibility is frequently included with a list of hardware requirements.

- Arduino nano controller
- Soil moisture sensor
- Ultrasonic sensor
- Metal sensor
- Jumper wires
- 5V Adapter
- LCD
- PCB (Printed Circuit board)
- Connecting wires
- Buzzer

5.2 Software Requirements:

The primary goal of software requirements is to determine which programs and system components are necessary for an application to run well on a given machine.

- Arduino IDE
- Embedded C
- Blynk Application

6. RESULTS

Typically, there are garbage cans scattered across the roadway, overflowing with excess waste. These scattered contaminants either burn or peak down or spill all over the place, putting human health at risk. The way that people dispose of their garbage has an impact on their health. This problem has been resolved with the development of an adequate waste segregation and monitoring system. Based on wireless communication, the Waste Segregation and Monitoring System is a creative approach to maintaining a clean and healthy city. Given the rapid growth of the global population, a higher standard of living depends on living in a clean and sanitary environment.




Fig.2. Automatic Smart Waste Management Existing Model




Fig.3. Proposed Output Experimental model Set up

An illustration of an innovative city waste segregation model is this one. The primary goal of this article is to deploy dustbins at the proper level and automatically segregate garbage using a wireless mesh network. This type of information helps cleaning businesses and litter bin providers make better selections for efficient disposal. Metal and moisture sensors detect metal and wet detritus, whereas ultrasonic sensors detect objects. Levels in the bin are monitored using an infrared sensor. After the garbage is placed in the bin, a sensor determines the type of waste. Each of the three portions of the container contains a distinct kind of garbage: the proper garbage collection and the proper walls. The location and current state of the bin are displayed in the smartphone message.



Fig.4: Display bin levels in LED

The hardware components, programming, and design employed in the construction of an automatic smart dustbin using Arduino might result in a range of different outputs. On the whole, however, a good automatic toilet flusher can provide several benefits:

1. **Improvement of Hygiene:** By eliminating the need for manual flushing, an automatic toilet flusher reduces the possibility of germ transmission and promotes a cleaner, more hygienic bathroom environment.
2. **Convenience:** Eliminating the need for manual toilet flushing increases use and convenience, especially in public restrooms and crowded areas.
3. **Energy Efficiency:** Over time, automatic flushers can be configured to use the least amount of electricity and money.



Fig.5. Experimental output Indicators

4. **User happiness:** A reliable, hands-free flushing mechanism can increase user happiness and promote a more pleasurable bathroom experience overall.




Fig.6. Automatic Alert Messages & their location.

5. **Alerts for Maintenance:** Many automated flusher systems include diagnostic capabilities that identify and notify maintenance staff of problems or maintenance needs to guarantee continuous functioning and dependability.

7. CONCLUSION

Innovative city development is an area that is seeing daily technical developments. Many things are getting in the way of those advancements. Inadequate garbage collection is one such obstacle. There was a lack of efficiency in using conventional methods. By primarily focusing on monitoring the level of garbage, the alternate technique presented in this research effectively collected waste, reduced human time and effort, and created a healthy environment. So, the suggested design prototype for an effective waste management method was executed without a hitch. This article will inspire others to investigate the waste management industry and come up with firm plans for the future. With the proper backing, this concept may quickly become a fully operational initiative for innovative city development. Fast data transfer via GSM and GPS makes this system's waste collecting mechanism more autonomous, according to it. One significant benefit of wireless protocols is that data may be transferred even while clients aren't physically present in the node network. Once a client is connected to that node, they can view the data that has already been sent. In order for them to keep tabs on garbage pickup as needed, The authorized individual receives updates on the position of these bins using GPS and GSM. They include dust, metal, and moist waste.

REFERENCES

1. Hitesh Poddar, Rituraj Paul, Sourangsu Mukherjee, Budhadev Bhattacharyya, "Design of Smart Bin For Smarter Cities," International Conference on Innovations in Power and Advanced Computing Technologies, 2017.
2. Aazam, Mohammad, "Cloud-based smart waste management for smart cities," Computer Aided Modelling and Design of Communication Links and Networks (CAMAD), 2016 IEEE 21st International Workshop on IEEE- 2016.
3. F.Folianto, Y.S.Low, and W.L.Yeow, "Smartbin: Smart waste management system," IEEE Tenth International Conference on Intelligent Sensors, Sensor Networks and Information Processing (ISSNIP), Singapore, 2015.
4. R. P. Meenakshi Sundhari, K. Jaikumar, "IoT assisted Hierarchical Computation Strategic Making (HCSM) and Dynamic Stochastic Optimization Technique (DSOT) for energy optimization in wireless sensor networks for smart city monitoring," Computer Communications 150 (2020) 226–234. <https://doi.org/10.1016/j.comcom.2019.11.032>
5. Miss. Megha S. Chaudhari, Mrs. Bharti Patil, "IoT-based Waste Collection Management System for Smart Cities," Third International Conference on Computing Methodologies and Communication (ICCMC 2019).

6. R. Ranjith Kumar and M. Bala Kumar, "A New Chaotic Image Encryption Using Parametric Switching Based Permutation and Diffusion," *ICTACT Journal on Image and Video Processing*, Vol. 4, No. 4, pp. 795-804, 2014.
7. Eyhab Al-Masri, Ibrahim Diabate, Richa Jain, Ming Hoi Lam, and Swetha Reddy Nathala "Recycle.io: An IoT-Enabled Framework for Urban Waste Management," 2018 IEEE International Conference on Big Data (Big Data)
8. Victor Vasconcelos Sobre, Davi L.de Oliveira, "Performance Evaluation of MQTT Brokers in the Internet of Things for Smart Cities" 4th International Conference on Smart and Sustainable Technologies (Spli Tech) on IEEE-2019.
9. K.C.T. Swamy, D. Venkata Ratnam, T. Suman, S. Towseef Ahmed, Time-differenced double difference method for measurement of Navigation with Indian Constellation (NavIC) receiver differential phase bias, *Measurement*, Volume 207, 15 February 2023, 112385, <https://doi.org/10.1016/j.measurement.2022.112385>.
10. Swamy KCT, Venkata Ratnam Devanaboyina, Tawseef Ahmed Shaik, Double difference method with zero and short base length carrier phase measurements for Navigation with Indian Constellation satellites L5 (1176.45 MHz) signal quality analysis, *International Journal of Satellite Communications and Networking*, Volume 40, Issue4, July/August 2022, Pages 294-304, <https://doi.org/10.1002/sat.1441>.
11. Swamy, K.C.T., Devanaboyina, Venkata Ratnam, Nallagarla, Ramamurthy, Shaik, Towseef Ahmed and Turpati, Suman. "Correlation between rate of TEC index and positioning error during solar flares and geomagnetic storms using navigation with Indian constellation receiver measurements," *Journal of Applied Geodesy*, 2024. <https://doi.org/10.1515/jag-2024-0022>.
12. U. Muthuraman, J. Monica Esther, R. Ravi, R. Kabilan, G. Prince Devaraj and J.ahariya Gabriel, "Embedded Sensor-based Construction Health Warning System for Civil Structures & Advanced Networking Techniques using IoT," *International Conference on Sustainable Computing and Data Communication Systems*, pp. 1002-1006, 2022.
13. D. priyadharshini, R. malliga@pandeeswari, S. Shargunam, and R. Ravi, "Internet of things: a comprehensive survey and perspective on recent works," *Francis Xavier Journal of Science Engineering and Management*, vol.1, no.1, pp.4-6, 2020.
14. D. A. García Arango, M. S. Echeverri Gutierrez, and C. M. Montoya Escobar, "Environmental Implications and Sustainability Challenges in BOPET-Based Flexible Packaging: A Circular Economy and Resource Management Analysis," *Journal of Experimental Biology and Agricultural Sciences*, vol. 14, no. 3, pp. 1–8, 2026. <https://jebas.org/ojs/index.php/jebas/article/view/3795>
15. J. C. Ayuque-Rojas, P. A. Palomino-Pastrana, V. G. Sánchez-Araujo, J. L. Huere-Peña, C. Dueñas-Jurado, E. J. Ccente-Chancha, R. Mejia-Cayllahua, B. E. Garcia-Riveros, H. Rodas-Ccopa, M. Y. Escobar-Soldevilla, and R. Yaulilahua-Huacho, "Development of a portable electrocoagulation unit for on-site treatment of washing machine wastewater," *Journal of Experimental Biology and Agricultural Sciences*, vol. 12, no. 5, pp. 676–685, 2024, doi: 10.18006/2024.12(5).676.685.
16. A. Ghatage, O. D. Chavan, and A. Jadhav, "Isolation and Detailed Characterization of Protease-Producing Bacteria Derived from Dairy Waste," *Bulletin of Pure and Applied Sciences-Zoology*, vol. 43B, no. 1S, pp. 344–357, 2024.
17. Geetanjali and A. R. Singh, "Precision and Smart Farming: An Approach to Efficient Resource Management in Agriculture," *Journal of Artificial Intelligence in Agriculture and Applied Research*, vol. 1, no. 1, pp. 25–33, 2025.
18. S. Masurkar, S. T. Bhalchandra, and A. Pathade, "Isolation and Characterization of Effective Microbial Cultures for Domestic Wastewater Treatment," *Bulletin of Pure and Applied Sciences-Zoology*, vol. 43B, no. 1S, pp. 644–655, 2024.
19. I. Sosunova and J. Porras, "IoT-Enabled Smart Waste Management Systems for Smart Cities: A Systematic Review," *IEEE Access*, vol. 10, pp. 73326–73363, 2022, <https://doi.org/10.1109/ACCESS.2022.3188308>.
20. Waste Monitoring. SENSONEO, 2019.
21. D. Misra, G. Das, T. Chakraborty, and D. Das, "An IoT-based waste management system monitored by cloud," *Journal of Material Cycles and Waste Management*, vol. 20, no. 3, pp. 1574–1582, Jul. 2018, <https://doi.org/10.1007/s10163-018-0720-y>.
22. C. S. Srikanth, T. B. Rayudu, J. Radhika, and R. Anitha, "Smart Waste Management using Internet-of-Things (IoT)," *International Journal of Innovative Technology and Exploring Engineering*, vol.8, no.9, pp.2518–2522, Jul.2019, <https://doi.org/10.35940/ijitee.G5334.078919>.
23. T. S. Vasagade, S. S. Tamboli, and A. D. Shinde, "Dynamic solid waste collection and management system based on sensors, elevator, and GSM," in 2017 International Conference on Inventive

- Communication and Computational Technologies (ICICCT), Coimbatore, India, Mar. 2017, pp. 263–267, <https://doi.org/10.1109/ICICCT.2017.7975200>.
24. A. Doshi, B. Shah, and J. Kamdar, "INTERNET: Smart Waste Management System," *International Journal for Research in Applied Science and Engineering Technology*, vol.9, no.6, pp. 703–707, Nov. 2021, <https://doi.org/10.22214/ijraset.2021.38882>.
 25. Ravi Chandra, B., Rakesh, N., Kumar, B.T.N., Praneeth, Y., Shaik, A. (2025). Smart Garbage Monitoring System Using IOT for Commercial Purposes. In: Mohanty, S.N., Satpathy, S., Cheng, X., Pani, S.K. (eds) *Explainable IoT Applications: A Demystification*. Information Systems Engineering and Management, vol 21. Springer, Cham. https://doi.org/10.1007/978-3-031-74885-1_17.
 26. Ravi Chandra, B., Tanusree, B., Sri Ramani, Y., Sowjanya, Y., Shaik, A. (2025). Block-Chain Technology in Smart Telemedicine Using IoT. In: Mohanty, S.N., Satpathy, S., Cheng, X., Pani, S.K. (eds) *Explainable IoT Applications: A Demystification*. Information Systems Engineering and Management, vol 21. Springer, Cham. https://doi.org/10.1007/978-3-031-74885-1_7